



## Typical Inspection Data:

Density @ 20°C	0.850 g/cm3
Viscosity @ 100°C	13.5 cSt
Viscosity @ 40°C	78 cSt
Viscosity Index	160
Viscosity CCS @ -30°C	6000 cP
T.B.N.	7.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.09%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

## X-Flow Type PD 5W-40 Fully Synthetic

### Recommended by Comma for applications requiring:

VW 505 01; FORD WSS-M2C917-A  
ACEA C3  
API SL CF

### Product Features:

- Fully synthetic 5W-40 oil for vehicles fitted with the VW 'Pumpe Duse' PD or unit injector engine.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [CommaOil.com](http://CommaOil.com)

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

28-10-2014