



## X-Flow Type G 5W-40 Fully Synthetic

### Recommended by Comma for applications requiring:

MB 229.1; VW 502 00, VW 505 00; RN0700, RN0710  
ACEA A3/B4  
API SL/CF

### Product Features:

- Fully synthetic 5W-40 oil suitable for petrol and diesel vehicles including those with fuel injected, multivalved and turbo charged engines.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [CommaOil.com](http://CommaOil.com)

### Typical Inspection Data:

Density @ 20°C	0.853 g/cm <sup>3</sup>
Viscosity @ 100°C	13.4 cSt
Viscosity @ 40°C	81 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	5900 cP
T.B.N.	10.6 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.13%
Calcium	0.11%
Phosphorus	0.11%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

27-07-2015