



X-Flow Type F Plus 5W-30

APPLICATION

- Fully synthetic 5W-30 oil for Ford petrol and diesel engines including Zetec and pre 2009 DuraTec and DuraTorq engines.
- Low viscosity to give fast oil flow on start up.

COMMA RECOMMENDS THIS PRODUCT FOR APPLICATIONS REQUIRING:

FORD WSS-M2C913-A, WSS-M2C913-B

ACEA A1/B1; API SL CF

(Suitable for Zetec, DuraTec & DuraTorq engines pre 2009)

TYPICAL INSPECTION DATA:

Specific gravity at 20°C	0.847
Viscosity @ 100°C	9.8 cSt
Viscosity @ 40°C	53 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	3900 cP
T.B.N.	7.8 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.11%
Calcium	0.26%
Phosphorus	0.11%
Colour	Brown
Flash Point	230 °C
Pour Point	-36 °C

HANDLING

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

SHELF LIFE

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

md 26-10-2012