



X-Flow Type P 5W-30

Fully Synthetic

Recommended by Comma for applications requiring:

PSA B71 2290
ACEA C2
API SM CF

Product Features:

- Fully synthetic 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C2 grade.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Typical Inspection Data:

Density @ 20°C	0.848 g/cm ³
Viscosity @ 100°C	11.2 cSt
Viscosity @ 40°C	65 cSt
Viscosity Index	169
Viscosity CCS @ -30°C	6300 cP
T.B.N.	7.0 mg KOH/g
Sulphated Ash Mass	0.7%
Zinc	0.09%
Calcium	0.17%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

28-10-2014