



Pro-NRG 0W-20

Fully Synthetic

Recommended by Comma for applications requiring:

API SN; ILSAC GF-4, GF-5

Product Features:

- Fully synthetic, high performance 0W-20 oil for modern petrol vehicles and most petrol-electric hybrids.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Typical Inspection Data:

Density @ 20°C	0.844
Viscosity @ 100°C	8.0 cSt
Viscosity @ 40°C	42 cSt
Viscosity Index	170
Viscosity CCS @ -35°C	5500 cP
T.B.N.	7.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.09%
Calcium	0.16%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-42°C

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

10-10-2014